

Zero Turn Mowers, Accu-Z Razor® Z44 & Z52 Series (S/N 526171+)

Features	Benefits
44" or 52" Cutting width	Sized and priced right for residential owners.
Ground speed	Forward 0-7 mph and Reverse 0-5 mph for high mowing productivity
Mid-mount deck design	Mid-mount design puts the deck closer to the operator's line of sight for a more efficient and precise operation.
Compact size	Enhances mowing maneuverability, as well as fitting on trailers or storing more efficiently.
Drive tire stance	Narrow width (44: 44", 52: 45") allows for tight turns in corners, yet gives a very stable platform for the operator.
Steering levers designed for more adjustment and comfort	Steering levers are designed with more adjustments to fit more comfortably to operators of all sizes. Also new comfort grip handles are standard equipment.
Stamped reinforcing ring added to deck construction	Makes a stronger deck and reduces unwanted flex.
Deck construction	Single welded frame design. 11 Gauge with 1" x 3/8" reinforcements.
Floating deck design	Deck has chain suspension which offers excellent flotation over uneven terrain.
Deck height adjustment	Height is changed by a spring-loaded foot operated lever and pin. Easier than hand levers to push and faster than waiting on an electric actuation.
Anti-scalp rollers - 4	Front middle and front corners to keep scalping to a minimum.
Cutting height	1 1/2" to 4 1/2" Range in 1/4" increments to cut any type of turf grass.
Tires	Wide tires offer excellent ground flotation. Heavy wheel forks take abuse.
High blade tip speed	44" = 16,811 fpm and 52" = 18,937 fpm (Assures a good finish cut.)
High lift blades	Heavy-duty high lift blades are .20" thick to handle the wear, with a high lift design to stand the grass up before cutting. Made from highest quality ™Marbain steel for longer blade life.
1" Blade spindles	1" Blades spindles with ball bearings handle heavy shock loads.
Single belt drive	Single belt design offers easier maintenance over multiple belt designs, less expensive to maintain.
Electric clutch control	Easy and smooth engagement of the mower blade drive system.
Hydro-Gear ZT-2800 TM (Zero-Turn Transaxle) drive unit on each rear wheel	Each mower has a homeowner friendly integrated hydrostatic transaxle containing a pump and drive motor for each rear wheel. Except for changing hydraulic filters, these units are self contained and are maintenance free.
Choice of Engines	Makes it possible for you to buy more value, performance and power for your dollar. 44" Deck: 22 hp Briggs & Stratton, 18 hp Honda 52" Deck: 22 & 26 hp Briggs & Stratton, 18 & 20 hp Honda
The engine is centered and oriented for maximum ease of service.	Engine orientation provides for increased air flow around engine fins to help extend engine life. Also it provides for a shorter overall mower length with more leg room available. Spark plugs, air cleaner, choke and throttle can be serviced from the rear verses the side. The muffler is located to reduce potential burn hazard and to lower sound level at the operator's station.
Electric start	Easily starts with the turn of a key.
Integrated fan blades	Pumps stay cool.
Sleek styling twin six-gallon molded fuel tanks with extra large inboard fuel caps.	Twin six-gallon tanks (12 gallons total) with selector valve for extending operating range and decreasing down time. Extra large fuel openings for easy fueling. Inboard positioning of fuel caps so they don't come off during operation.
Molded-in dual cup holders and storage compartments	Cup holders fit a wide variety of cups and are in easy access to driver. Storage compartments offer additional operator convince.
Seat options	Molded seat incorporates a high back to give adequate comfort for the long jobs or Deluxe Cushion seat for additional suspension over rough terrain.
Integrated park brake	Spread steering levers fully out; this automatically sets the Park Brake. No separate lever to hunt for.

Designs, specifications, features and information are subject to change without notice.

4/14/08 357-187F 84